

## BOSCH EDC17CP18 IROM TC1797 GPT CHEVROLET GMC

plugin 950 BOSCH EDC17CP18 IROM TC1797 GPT CHEVROLET  
GMC

### **GPT CONNECTION MODE**


To perform the GPT connection it is necessary to use both the ANALOG PORT and the DIGITAL PORT.

### **GPT connection with loose wires**

Connect the F32GN037 cable to the **ANALOG PORT**

Connect the F34NTA15 to the **DIGITAL PORT**, use the YELLOW and ORANGE wires for the GPT signals, WHITE and GREEN for the second CAN line as displayed in the following pictures.

### **F34NTA15**




BOSCH EDC17CP18 IROM TC1797 GPT CHEVROLET GMC

EDC17CP18 (E86)



BOSCH EDC17CP18 IROM TC1797 GPT CHEVROLET GMC




## BOSCH EDC17CP18 IROM TC1797 GPT CHEVROLET GMC

### ECU CONNECTOR

For the connection use the cable F32GN037C connected to the ECU.  
Make sure that the POWER led (red) on Trasdata is ON.

COLORE FILO WIRE COLOUR	DESCRIZIONE DESCRIPTION
ROSSO RED	POSITIVO DIRETTO POWER BATTERY
ARANCIO ORANGE	POSITIVO SOTTO QUADRO POWER SWITCH ON
NERO BLACK	MASSA GND
GIALLO YELLOW	KLINE
VERDE GREEN	CAN LOW
BIANCO WHITE	CAN HIGH
GRIGIO GREY	POL4 BOOT
BLU BLUE	POL5 CNF1
VIOLA/GRIGIO PURPLE/GREY	TENSIONE PROG. PROG. VOLTAGE
MARRONE BROWN	RESET




### DIRECT GPT CONNECTION

GPT connection is required for the first time only, after the first ECU reading it is not necessary any longer. Connect the F34NTA15 flat cable to the GPT S1, GPT S2 and CAN 2L, CAN2H pins.

PIN / Colore PIN / Color	DESCRIZIONE DESCRIPTION
	GPT_S2
	GPT_S1
	CAN 2H
	CAN 2L

BOSCH EDC17CP18 IROM TC1797 GPT CHEVROLET GMC



## BOSCH EDC17CP18 IROM TC1797 GPT CHEVROLET GMC

### DIRECT BOOT CONNECTION

Connect the GREY wire of the cable F32GN037C as shown in the picture.

COLORE FILO WIRE COLOUR	DESCRIZIONE DESCRIPTION
GRIGIO	POL4
GREY	BOOT

