
plugin 680

MEC37-900 NISSAN




MEC37-900 B1 1126
Hitachi Automotive Systems
Europe Ltd (UK)



#### **DIRECT CONNECTION**

For the connection with LOOSE WIRES use the cable F32GN037C connected to the ECU. Do NOT use this connection for the DIMA.

COLORE FILO WIRE COLOUR		DESCRIZIONE DESCRIPTION	
	ROSSO RED	POSITIVO DIRETTO POWER BATTERY	
	ARANCIO ORANGE	POSITIVO SOTTO QUADRO POWER SWITCH ON	
	NERO BLACK	MASSA GND	
	GIALLO YELLOW	KLINE	
	VERDE GREEN	CAN LOW	
	BIANCO WHITE	CAN HIGH	
	GRIGIO GREY	POL4 BOOT	
	BLU BLUE	POL5 CNF1	
	VIOLA/GRIGIO PURPLE/GREY	TENSIONE PROG. PROG. VOLTAGE	
	MARRONE BROWN	RESET	



## **ECU CONNECTOR**




## **DIRECT CONNECTION - ECU READING:**


For the READING procedure use the FLAT cable F34NTF53, you have to connect the wiring on both sides of the ECU.

	1 25 2 26	
Pin	Colore Colour	
11	Non usato Not used	
1.2	Non usato	
1.4	Not used	
13	Non usato Not used	
	Not used Non usato	
14	Not used	
15	Non usato	
A SAME	Not used Blu	
16	Blue	
17	Viola	
17	Violet	
18	Grigio Grey	
10	Bianco	
19	White	
20	Nero	
40.00	Black	
21	Marrone	
	Brown Rosso	
2.2	Red	
23	Arancio	
23	Orange Giallo	
24		
25	Yellow Verde	
25	Green	
26	Non usato Not used	

# Microprocessor side



## Opposite side



## **DIRECT CONNECTION - ECU WRITING:**

For the WRITING procedure use the FLAT cable F34NTF51

